

View Online at <https://aerobasegroup.com/nsn/4720-00-056-9085>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.391 inches and 0.421 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 500.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.546 inches and 0.585 inches

**Minimum Inside Bending Radius:**

4.625 inches

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

8000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

24.000 inches working

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved sources 96906 have indicated thier part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0