NSN 4720-00-058-2589

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-058-2589 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.625 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.781 inches **Minimum Inside Bending Radius:** 6.500 inches Angle Between Rigid Elbow Fittings In Deg: 235.0 **End Connection Design:** Elbow 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2000.0 pounds per square inch Flow Angle: 45.0 degrees 1st end **Outer Covering Environmental Protection:** Corrosion resistant **Vacuum In Torr:** 50.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 43.625 inches working

Shelf Life: N/a

NSN 4720-00-058-2589

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0