## NSN 4720-00-058-4089



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-058-4089 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.219 inches **Tempurature Rating:** -67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.313 inches **Minimum Inside Bending Radius:** 3.000 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 16000.0 pounds per square inch **Layer Composition And Location:** 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant steel wire and 1st layer braided copper wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Flow Angle: 45.0 degrees 2nd end **Outer Covering Environmental Protection:** Corrosion resistant

Inside Surface Condition: Smooth

**Measuring Method And Length:** 

15.500 inches working

**Thread Series Designator:** 

Unif 1st end

Shelf Life:

N/a

## NSN 4720-00-058-4089

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0