

NSN 4720-00-060-1044 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-060-1044 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.485 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability and nuts drilled for lockwire

**Burst Test Pressure:** 

7000.0 pounds per square inch

**Layer Composition And Location:** 

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:** 

1500.0 pounds per square inch

**Thread Size:** 

0.875 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

**Hydrostatic Test Pressure:** 

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

15.500 inches working

**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 4720-00-060-1044

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0