## NSN 4720-00-061-7474

**Cross Sectional Shape:** 

Round

**Thread Class:** 

3b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-061-7474

| Thread Direction:   |
|---|
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.125 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.250 inches  |
| Minimum Inside Bending Radius:  |
| 1.500 inches  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Features Provided:  |
| Electrostatic discharge capability  |
| Burst Test Pressure:  |
| 12000.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 1500.0 pounds per square inch   |
| Thread Size:  |
| 0.375 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 3000.0 pounds per square inch   |
| Vacuum In Torr:   |
| 50.8  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 19.250 inches working   |
| Special Features:   |
| Manufactured in accordance w/aso standard dwg aso-to586                               |
| Thread Series Designator:   |
| Unf 1st end   |

## NSN 4720-00-061-7474

Nonmetallic Hose Assembly - Page 2 of 2



| Spec | ifica | ation | Data: |
|------|-------|-------|-------|
|------|-------|-------|-------|

81349-mil-h-25579 government specification

**Specification Or Standard:** 

3 size

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0