## NSN 4720-00-062-1548

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-062-1548 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.875 inches **Outside Diameter:** 1.234 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 3200.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 800.0 pounds per square inch **Thread Size:** 1.312 inches 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 108.000 inches working Media For Which Designed: Hydraulic fluid single response **Thread Series Designator:** Unj 1st end **Specification Data:** 96906-ms28741 government standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 4720-00-062-1548

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0