## NSN 4720-00-062-4158

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-062-4158

Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.312 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.437 inches Connection Style: Swivel nut, inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cross Sectional Shape:
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.312 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.437 inches Connection Style: Swivel nut, inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.312 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.437 inches Connection Style: Swivel nut, inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Thread Direction: Right-hand 1st end Inside Diameter: 0.312 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.437 inches Connection Style: Swivel nut, inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Right-hand 1st end Inside Diameter:  0.312 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter:  0.437 inches Connection Style: Swivel nut, inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Inside Diameter:  0.312 inches  Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response  Outside Diameter:  0.437 inches  Connection Style: Swivel nut, inverted flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
0.312 inches  Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response  Outside Diameter: 0.437 inches  Connection Style: Swivel nut, inverted flare 1st end  End Connection Design: Straight 1st end  Connection Type: Threaded internal tube 1st end  Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch  Thread Size: 0.562 inches 1st end  Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth  Measuring Method And Length: 126.000 inches working  Thread Series Designator: Unf 1st end  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	-
Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response  Outside Diameter: 0.437 inches  Connection Style: Swivel nut, inverted flare 1st end End Connection Design: Straight 1st end  Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response  Outside Diameter:  0.437 inches  Connection Style: Swivel nut, inverted flare 1st end  End Connection Design: Straight 1st end  Connection Type: Threaded internal tube 1st end  Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch  Thread Size: 0.562 inches 1st end  Seat Angle: 24.0 degrees 1st end  Inside Surface Condition: Smooth  Measuring Method And Length: 126.000 inches working  Thread Series Designator: Unf 1st end  Shelf Life: N/a  Unit Of Measure: Demilitarization: No	
Outside Diameter:  0.437 inches  Connection Style: Swivel nut, inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
O.437 inches  Connection Style: Swivel nut, inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Connection Style:  Swivel nut, inverted flare 1st end  End Connection Design:  Straight 1st end  Connection Type:  Threaded internal tube 1st end  Layer Composition And Location:  Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.562 inches 1st end  Seat Angle:  24.0 degrees 1st end  Inside Surface Condition:  Smooth  Measuring Method And Length:  126.000 inches working  Thread Series Designator:  Unf 1st end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	
Swivel nut, inverted flare 1st end  End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Straight 1st end  Connection Type: Threaded internal tube 1st end  Layer Composition And Location: Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure: 1500.0 pounds per square inch  Thread Size: 0.562 inches 1st end  Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth  Measuring Method And Length: 126.000 inches working  Thread Series Designator: Unf 1st end  Shelf Life: N/a  Unit Of Measure: Demilitarization: No	
Connection Type: Threaded internal tube 1st end Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	End Connection Design:
Threaded internal tube 1st end  Layer Composition And Location:  Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.562 inches 1st end  Seat Angle:  24.0 degrees 1st end  Inside Surface Condition:  Smooth  Measuring Method And Length:  126.000 inches working  Thread Series Designator:  Unf 1st end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Straight 1st end
Layer Composition And Location:  Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.562 inches 1st end  Seat Angle:  24.0 degrees 1st end  Inside Surface Condition:  Smooth  Measuring Method And Length:  126.000 inches working  Thread Series Designator:  Unf 1st end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Connection Type:
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.562 inches 1st end  Seat Angle:  24.0 degrees 1st end  Inside Surface Condition:  Smooth  Measuring Method And Length:  126.000 inches working  Thread Series Designator:  Unf 1st end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Threaded internal tube 1st end
Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.562 inches 1st end  Seat Angle:  24.0 degrees 1st end  Inside Surface Condition:  Smooth  Measuring Method And Length:  126.000 inches working  Thread Series Designator:  Unf 1st end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Layer Composition And Location:
1500.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Outer layer braided corrosion resistant steel wire
Thread Size:  0.562 inches 1st end  Seat Angle:  24.0 degrees 1st end  Inside Surface Condition:  Smooth  Measuring Method And Length:  126.000 inches working  Thread Series Designator:  Unf 1st end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Maximum Operating Pressure:
0.562 inches 1st end  Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth  Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	1500.0 pounds per square inch
Seat Angle: 24.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Thread Size:
24.0 degrees 1st end Inside Surface Condition: Smooth  Measuring Method And Length: 126.000 inches working Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.562 inches 1st end
Inside Surface Condition:  Smooth  Measuring Method And Length:  126.000 inches working  Thread Series Designator:  Unf 1st end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Seat Angle:
Smooth  Measuring Method And Length:  126.000 inches working  Thread Series Designator:  Unf 1st end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	24.0 degrees 1st end
Measuring Method And Length:  126.000 inches working  Thread Series Designator:  Unf 1st end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Inside Surface Condition:
126.000 inches working  Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Smooth
Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Measuring Method And Length:
Unf 1st end  Shelf Life: N/a Unit Of Measure: Demilitarization: No	126.000 inches working
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No	Unf 1st end
Unit Of Measure: Demilitarization: No	Shelf Life:
Demilitarization:	N/a
No	Unit Of Measure:
No	<u></u>
	Demilitarization:
Fiig:	No
	Fiig:
A542a0	A542a0