

NSN 4720-00-062-6822 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-062-6822 **Cross Sectional Shape:** Round **Thread Class:** 

3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.312 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 

0.438 inches

**Minimum Inside Bending Radius:** 

4.000 inches

**Exterior Color:** 

Natural

**Connection Style:** 

Swivel nut flare 1st end

**End Connection Design:** 

Straight 1st end

**Connection Type:** 

Threaded internal tube 1st end

**Burst Test Pressure:** 

9000.0 pounds per square inch

**Layer Composition And Location:** 

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:** 

1500.0 pounds per square inch

**Thread Size:** 

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

**Hydrostatic Test Pressure:** 

3000.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Corrosion resistant

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

49.000 inches working

**Thread Series Designator:** 

Unf 1st end

## NSN 4720-00-062-6822

Nonmetallic Hose Assembly - Page 2 of 2



S	ne	cifi	catio	on F	)ata
J	υe	CIII	Cali	UII L	ıala

81349-mil-h-25579 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0