## NSN 4720-00-062-7214

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-062-7214

-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.562 inches
Minimum Inside Bending Radius:
4.625 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.7F0 inches dat and
0.750 inches 1st end
Seat Angle:
Seat Angle:
Seat Angle: 37.0 degrees 1st end
Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure:
Seat Angle: 37.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch
Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection:
Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant
Seat Angle: 37.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant  Inside Surface Condition:
Seat Angle: 37.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant  Inside Surface Condition:  Smooth
Seat Angle:  37.0 degrees 1st end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:
Seat Angle:  37.0 degrees 1st end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:  360.000 inches working
Seat Angle:  37.0 degrees 1st end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant  Inside Surface Condition:  Smooth  Measuring Method And Length:  360.000 inches working  Thread Series Designator:
Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 360.000 inches working Thread Series Designator: Unjf 1st end

## NSN 4720-00-062-7214

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No Fiig:

Mil-std (military Standard):

Mil-h-25579 spec.