NSN 4720-00-062-9864

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-062-9864

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.298 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
0.618 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant steel wire and 1st layer spirally laid
steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
8.250 inches working

NSN 4720-00-062-9864

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0