## NSN 4720-00-062-9865



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-062-9865 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.212 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.505 inches **Minimum Inside Bending Radius:** 3.000 inches **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 16000.0 pounds per square inch **Layer Composition And Location:** 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant steel wire and 1st layer spirally laid steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end **Hydrostatic Test Pressure:** 8000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 9.000 inches working **Thread Series Designator:** 

**Unit Of Measure:** 

N/a

Unjf 1st end Shelf Life:

## NSN 4720-00-062-9865

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0