

View Online at <https://aerobasegroup.com/nsn/4720-00-064-2681>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

0.312 inches

Minimum Inside Bending Radius:

2.000 inches

Angle Between Rigid Elbow Fittings In Deg:

53.0

Hose Or Tubing Specification/std Data:

Mil-h-27267 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Mil ms27060 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Connection Design:

Elbow 1st end

End Fitting Component And Material:

Nut stainless steel 2nd end

Fitting Component And Surface Treatment:

Nut passivate 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

20 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Corrosion resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

5.300 inches working

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Media For Which Designed:

Air and alcohol, ethyl and alcohol, methyl and fuel/oil, hydrocarbon and water, fresh and water, salt single response

Thread Series Designator:

Unf 1st end

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-27267 spec.