Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-064-3451

Cross	Sectional	Shape:
-------	-----------	--------

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.125 inches

Tempurature Rating:

-100.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

1.359 inches

Minimum Inside Bending Radius:

11.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

1.625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.000 inches working

Thread Series Designator:

Unj 1st end

NSN 4720-00-064-3451

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

