Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-064-6436

| Cros | s Sectional Shape: |
|--------|---|
| Roun | |
| Threa | ad Class: |
| 2b 1s | st end |
| Threa | ad Direction: |
| Riaht | -hand 1st end |
| - | e Diameter: |
| | 5 inches |
| Temr | ourature Rating: |
| - | degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| | ide Diameter: |
| 0.890 |) inches |
| Minir | num Inside Bending Radius: |
| |) inches |
| Conr | nection Style: |
| | el nut flare 2nd end |
| End (| Connection Design: |
| | ght 1st end |
| Conr | nection Type: |
| Threa | aded internal tube 1st end |
| Threa | ady Qty Per Inch (tpi): |
| 12 2n | nd end |
| Burs | t Test Pressure: |
| 5000. | .0 pounds per square inch |
| Laye | r Composition And Location: |
| Outer | r layer braided corrosion resistant steel wire |
| Maxi | mum Operating Pressure: |
| 1000. | .0 pounds per square inch |
| Threa | ad Size: |
| 1.062 | 2 inches 2nd end |
| Seat | Angle: |
| 37.0 | degrees 2nd end |
| Hydr | ostatic Test Pressure: |
| 2000. | .0 pounds per square inch |
| Flow | Angle: |
| 90.0 (| degrees 2nd end |
| Insid | e Surface Condition: |
| Smoo | oth |
| Meas | suring Method And Length: |
| 11.50 | 00 inches working |
| Threa | ad Series Designator: |
| 11-0- | nd end |

NSN 4720-00-064-6436

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

