

View Online at <https://aerobasegroup.com/nsn/4720-00-064-7568>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.000 inches

Outside Diameter:

1.500 inches

Minimum Inside Bending Radius:

6.000 inches

Hose Or Tubing Specification/std Data:

Zz-h-561, grade a, type 2, class 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Connection Style:

Plain 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting zinc 1st end

Connection Type:

Threaded external pipe 1st end

Second End Relationship With First End:

Identical

First End Swivel Action Capability:

Not included

Layer Composition And Location:

2nd layer helix wire coil

Thread Size:

1.000 inches 1st end

Hydrostatic Test Pressure:

100.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and ozone resistant and weatherproof

Vacuum In Torr:

254.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

180.000 inches excluding end fittings

Special Features:

Inner conveying tube material-rubber, synthetic; furnished with two internal threaded swivel joints and one strainer

Media For Which Designed:

Water, salt single response

Thread Series Designator:

Npt 1st end

Specification Data:

Zz-h-561, grade a, type 2, class 1 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0