Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-065-1910

Round

Thread Class:

2b 1st end

# Thread Direction:

Right-hand 1st end

# Inside Diameter:

0.312 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.610 inches

Minimum Inside Bending Radius:

#### 1.250 inches

**Exterior Color:** 

Black

### **Connection Style:**

Swivel nut flare 1st end

#### **End Connection Design:**

Straight 1st end

### Connection Type:

Threaded internal tube 1st end

### **Features Provided:**

Reusable end fittings

### **Burst Test Pressure:**

6000.0 pounds per square inch

### Layer Composition And Location:

2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated fabric and 1st layer braided fabric

### Maximum Operating Pressure:

1500.0 pounds per square inch

#### Thread Size:

0.625 inches 1st end

#### Seat Angle:

45.0 degrees 1st end

#### Hydrostatic Test Pressure:

3000.0 pounds per square inch

# Inside Surface Condition:

Smooth

# Measuring Method And Length:

28.500 inches

### Media For Which Designed:

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

