

View Online at <https://aerobasegroup.com/nsn/4720-00-065-8639>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.321 inches and 0.398 inches

Temperature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.477 inches and 0.641 inches

Minimum Inside Bending Radius:

2.500 inches

Angle Between Rigid Elbow Fittings In Deg:

90.0

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Elbow 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

600.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

Outer layer molded rubber, synthetic

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

300.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

33.000 inches working

Special Features:

Inner conveying tube material-rubber, buna-n

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0