Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-065-8674

	ional Shape:
Round	
Thread Dire	
Right-hand	
Inside Dian	neter:
0.188 inche	S
Tempuratu	re Rating:
-40.0 degree	es fahrenheit and 250.0 degrees fahrenheit single response
Outside Dia	ameter:
Between 0.3	344 inches and 0.375 inches
Minimum Ir	nside Bending Radius:
1.000 inche	S
Connectior	n Style:
Plain 1st en	d
End Conne	ction Design:
Straight 1st	end
Connectior	а Туре:
Threaded ex	xternal hose 1st end
Thready Qt	y Per Inch (tpi):
27 1st end	
Burst Test	Pressure:
1600.0 pour	nds per square inch
Layer Com	position And Location:
Outer layer	molded rubber, synthetic and 1st layer braided rayon cord
Maximum (Operating Pressure:
400.0 pound	ds per square inch
Thread Size	2:
0.125 inche	s 1st end
Inside Surf	ace Condition:
Smooth	
Measuring	Method And Length:
8.700 inche	
Media For V	Which Designed:
	ylene glycol and fuel/oil, hydrocarbon and hydraulic fluid and fuel/oil, hydrocarbon and water single respons
	ies Designator:
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Mea	
 Demilitariza	ation

NSN 4720-00-065-8674

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

