NSN 4720-00-065-9626



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-065-9626 **Cross Sectional Shape:** Round **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.580 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** Inverted flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal and external tube 2nd end Thready Qty Per Inch (tpi): 16 2nd end **Burst Test Pressure:** 11000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided steel wire **Maximum Operating Pressure:** 2750.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 5500.0 pounds per square inch **Inside Surface Condition:** Smooth

Measuring Method And Length:

15.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-00-065-9626

Nonmetallic Hose Assembly - Page 2 of 2



		•		
Ιh	read	Series	Desiar	nator:

Unf and un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0