Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-066-8979

C	cross Sectional Shape:
R	tound
Т	hread Class:
3	b 1st end
Т	hread Direction:
R	light-hand 1st end
lr	nside Diameter:
0	.188 inches
т	empurature Rating:
-6	65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
0	Outside Diameter:
0	.312 inches
N	Iinimum Inside Bending Radius:
2	.000 inches
С	connection Style:
S	wivel nut, flareless 2nd end
E	nd Connection Design:
S	traight 1st end
С	Connection Type:
Т	hreaded internal tube 1st end
F	eatures Provided:
E	lectrostatic discharge capability
т	hready Qty Per Inch (tpi):
2	0 1st end
В	Burst Test Pressure:
1	2000.0 pounds per square inch
L	ayer Composition And Location:
С	Outer layer braided corrosion resistant steel wire
N	laximum Operating Pressure:
1	500.0 pounds per square inch
т	hread Size:
0	.438 inches 1st end
S	eat Angle:
1	2.0 degrees 2nd end
Н	lydrostatic Test Pressure:
6	000.0 pounds per square inch
F	low Angle:
9	0.0 degrees 2nd end
۷	acuum In Torr:
5	0.8
lr	nside Surface Condition:
~	mooth



Measuring Method And Length: 9.750 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0