## NSN 4720-00-067-3302

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-067-3302	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.391 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response	
Outside Diameter:	
Between 0.585 inches and 0.615 inches	
Minimum Inside Bending Radius:	
2.875 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
14000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Corrosion resistant	
Incide Surface Conditions	

Inside Surface Condition:

Smooth

**Measuring Method And Length:** 

23.375 inches

**Thread Series Designator:** 

Unjf 1st end

## NSN 4720-00-067-3302

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:
81343-as153 professional/industrial association standard
Shelf Life:
N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-38360 spec.