NSN 4720-00-067-4779 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-067-4779 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end

Tempurature Rating:

Inside Diameter: 0.298 inches

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

Between 0.455 inches and 0.490 inches

Minimum Inside Bending Radius:

2.500 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

14000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.750 inches

Thread Series Designator:

Unjf 1st end

NSN 4720-00-067-4779

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:
81343-as153 professional/industrial association standard
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-38360 spec.