## NSN 4720-00-067-4781

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-067-4781
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.298 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
Between 0.455 inches and 0.490 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:

Corrosion resistant

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

20.250 inches

**Thread Series Designator:** 

Unjf 1st end

## NSN 4720-00-067-4781

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:
81343-as153 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Mil-std (military Standard):

Mil-h-38360 spec.

**Fiig:** A542a0