NSN 4720-00-067-4788

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.298 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-067-4788

Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
Between 0.455 inches and 0.490 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
23.500 inches
Thread Series Designator:
Unjf 1st end

NSN 4720-00-067-4788

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

82343-as153 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0