Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-067-5084

Creas Sastianal Shana	
Cross Sectional Shape: Round	
Thread Class: 3b 1st end	
Thread Direction:	
Right-hand 1st end Inside Diameter:	
0.188 inches	
Tempurature Rating:	
-100.0 degrees fahrenheit and 450.0 degrees fahrenheit single response Outside Diameter:	
0.312 inches	
Minimum Inside Bending Radius: 2.000 inches	
Connection Style: Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire and 1st layer spirally laid corrosion resistant steel wire	
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
45.0 degrees 2nd end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Flow Angle:	
45.0 degrees 2nd end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
12.000 inches working	
Thread Series Designator:	
Unjf 1st end	

NSN 4720-00-067-5084

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

