

View Online at <https://aerobasegroup.com/nsn/4720-00-067-5733>

Cross Sectional Shape:

Round

Inside Diameter:

1.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Flange Thickness:

0.300 inches 2nd end

Outside Diameter:

1.704 inches

Minimum Inside Bending Radius:

9.000 inches

Exterior Color:

Natural

Angle Between Rigid Elbow Fittings In Deg:

192.0

Center To Center Distance Between Bolt Holes Along Width:

1.800 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.800 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.386 inches 2nd end

Flange Width:

2.386 inches 2nd end

Connection Style:

Plain swivel 2nd end

Bolt Hole Diameter:

0.273 inches 2nd end

End Flange Construction:

Split 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

3200.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

800.0 pounds per square inch

Hydrostatic Test Pressure:

1600.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.250 inches working

Flange Style:

Rectangular (includes square) 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources 00624 have indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0