NSN 4720-00-067-5828

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-067-5828

| Inside Diameter: | | | | | |
|---|--|--|--|--|--|
| 0.391 inches | | | | | |
| Tempurature Rating: | | | | | |
| -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response | | | | | |
| Outside Diameter: | | | | | |
| 0.765 inches | | | | | |
| Minimum Inside Bending Radius: | | | | | |
| 2.880 inches | | | | | |
| Connection Style: | | | | | |
| Swivel nut flare 1st end | | | | | |
| End Connection Design: | | | | | |
| Straight 1st end | | | | | |
| Connection Type: | | | | | |
| Threaded internal tube 1st end | | | | | |
| Features Provided: | | | | | |
| Electrostatic discharge capability | | | | | |
| Burst Test Pressure: | | | | | |
| 14000.0 pounds per square inch | | | | | |
| Layer Composition And Location: | | | | | |
| Outer layer braided corrosion resistant steel wire | | | | | |
| Maximum Operating Pressure: | | | | | |
| 3000.0 pounds per square inch | | | | | |
| Thread Size: | | | | | |
| 0.750 inches 1st end | | | | | |
| Seat Angle: | | | | | |
| 37.0 degrees 1st end | | | | | |
| Hydrostatic Test Pressure: | | | | | |
| 6000.0 pounds per square inch | | | | | |
| Outer Covering Environmental Protection: | | | | | |
| Corrosion resistant | | | | | |
| Inside Surface Condition: | | | | | |
| Smooth | | | | | |
| Measuring Method And Length: | | | | | |
| 16.750 inches working | | | | | |
| Thread Series Designator: | | | | | |
| Unjf 1st end | | | | | |

NSN 4720-00-067-5828

Nonmetallic Hose Assembly - Page 2 of 2



| S | pec | ific | cati | on | Data: |
|---|-----|------|------|----|-------|
| | | | | | |

81343-as153 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0