

View Online at <https://aerobasegroup.com/nsn/4720-00-067-8051>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.688 inches

**Temperature Rating:**

-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

**Outside Diameter:**

1.062 inches

**Minimum Inside Bending Radius:**

7.750 inches

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel comp 304 all ends

**Fitting Component And Surface Treatment:**

Complete fitting passivate 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 2nd end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

12000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer spirally laid corrosion resistant steel wire

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

1.062 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

37.500 inches working

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-plastic, polytetrafluoroethylene

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved sources 81343 have indicated thier part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Thread Series Designator:**

Unj 2nd end

**Specification Data:**

81343-as629 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0