Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-067-8697

Cross Sectional Shape: Round Round Fread Class: 2 bits end Thread Direction: Right-hand 1st end Inside Diameter: 0.688 inches Tempurature Rating: 40.0 degrees tharenheit and 300.0 degrees fahrenheit single response Outside Diameter: 1.031 inches Minimum Inside Bending Radius: 6.500 inches Exterior Color: Natural Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Freadure Rating: Connection Type: Thread Bits end Freadure Rating: 1.031 inches Riterion Type: Thread Straige capability Thread Per Inch (tpi): 12 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Riteria Straige: 1.032 inches 1st end Fread Straige: 1.033 inches Fread Straige: 1.034 inches Fread Straige: 1.035 inches Fread Straige: 1.030 inches Fre	
Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.688 Inches Tempurature Rating: -4.0.0 degrees fahrenheit and 300.0 degrees fahrenheit single response Outside Diameter: 1.031 Inches Minimum Inside Bending Radius: 0.500 Inches Exterior Color: Natural Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Design: Straight 1st end Connection Type: Threade Internal tube 1st end Features Provide: Electrostatic discharge capability Thready QP Per Inch (tpi): 12 1st end Eust Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximu Operating Pressure: 100.0 pounds per square inch Entred Size: 1.062 inches 1st end Set Angie: 3.7.0 degrees 1st end Midrostatic Test Pressure: 200.0 pounds per square inch Midrostatic Test Pressure: 200.0 pounds per square inch	Cross Sectional Shape:
2) Istend         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.688 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response         Outside Diameter:         1.031 inches         Minimun Inside Bending Radius:         6.500 inches         Exterior Color:         Natural         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Threade y per Inch (tp):         12 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic         Maximu Operating Pressure:         1.062 inches 1st end         Steat Angle:         3.7.0 degrees 1st end         Steat Angle:         3.7.0 degrees 1st end         Outer Covering Environmental Protection:         200.0 pounds per square inch </td <td>Round</td>	Round
Thread Direction:         Right-hand 1st end         Inside Diameter:         0.688 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response         Outside Diameter:         1.031 inches         Minimum Inside Bending Radius:         6.500 inches         Exterior Color:         Natural         Connection Design:         Swiel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Thread Utbe 1st end         Features Provided:         Electrostatic discharge capability         Thready Utp Per Inch (tpi):         12 1st end         Burst Test Pressure:         1000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic         Maximum Operating Pressure:         100.0.0 pounds per square inch         Straight 1st end         Straight 2st end         Burst Test Pressure:         100.0 pounds per square inch         Cuter layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic         Maximum Operating	Thread Class:
Right-hand 1st end         Inside Diameter:         0.688 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response         Outside Diameter:         1.031 inches         Minimun Inside Bending Radius:         6.500 inches         Exterior Color:         Natural         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Thready Oty Per Inch (tpi):         12 1st end         Burst Test Pressure:         1000.0 pounds per square inch         Layer Composition And Location:         1000.0 pounds per square inch         Straight 1st end         Straight 1st end         Burst Test Pressure:         1000.0 pounds per square inch         Layer Composition And Location:         1000.0 pounds per square inch         Straight 1st end         Straight 1st end         Straight 1st end         Duter layer braided corrosion resistant stel wire and 1st layer molded rubber, synthet	2b 1st end
Inside Diameter: Unside	Thread Direction:
0.888 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response         Outside Diameter:         1.031 inches         Minimum Inside Bending Radius:         6.500 inches         Exterior Color:         Natural         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded infernal tube 1st end         Freatures Provided:         Electrostatic discharge capability         Thready Oty Per Inch (tpi):         12 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic         Maximum Operating Pressure:         1.062 inches 1st end         Pressol Ext end         Hydrostic Test Pressure:         1.062 inches 1st end         Set Angle:         2.0 degrees 1st end         Hydrostic Test Pressure:         2.00.0 pounds per square inch         Coter covering Environmental Protection:         2.00.0 pounds per square inch	Right-hand 1st end
Tempurature Rating:         -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response         Outside Diameter:         1.031 inches         Minimum Inside Bending Radius:         6.500 inches         Exterior Color:         Natural         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Threaded internal tube 1st end         Foury Outp Per Inch (tpi):         12 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic         Maximum Operating Pressure:         1.062 inches 1st end         Stat Angle:         2.10 degrees 1st end         Hydrostatic Test Pressure:         2.00.0 pounds per square inch         Chread Size:         2.0.0 pounds per square inch         Durous per square inch         Stat Angle:         2.10 degrees 1st end         Hydros	Inside Diameter:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response         Outside Diameter:         1.031 inches         Minimum Inside Bending Radius:         6.500 inches         Exterior Color:         Natural         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic         Maximum Operating Pressure:         1.062 inches 1st end         Streed Steel         1.062 inches 1st end         Pressure:         1.062 inches 1st end         Streed Steel         1.062 inches 1st end         Pressure:         1.000.0 pounds per square inch         Hayer         1.062 inches 1st end         Steet Angle:         37.0 degrees 1st end         Hydrostat	0.688 inches
Outside Diameter:         1.031 inches         Minimum Inside Bending Radius:         6.500 inches         Exterior Color:         Natural         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic         Maximum Operating Pressure:         1.062 inches 1st end         Streed Steel         1.062 inches 1st end         Pressure:         1.062 inches 1st end         Streed Steel         1.062 inches 1st end         Diodo pound	Tempurature Rating:
1.031 inches         Minimum Inside Bending Radius:         6.500 inches         Exterior Color:         Natural         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         000.0 pounds per square inch         Maximum Operating Pressure:         1000.0 pounds per square inch         Straight 1st end         Mound poerating Pressure:         1000.0 pounds per square inch         Layer Composition And Location:         000.0 pounds per square inch         Hered Size:         1.062 inches 1st end         Stert Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         200.0 pounds per square inch         Outer Lovering Environmental Protection:         200.0 pounds per square inch	-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Minimum Inside Bending Radius:         6:500 inches         Exterior Color:         Natural         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         000.0 pounds per square inch         Maximum Operating Pressure:         1000.0 pounds per square inch         Straigen:         1.062 inches 1st end         Pressure:         1.002.0 pounds per square inch         Hered Size:         1.062 inches 1st end         Stratest Pressure:         1.062 inches 1st end         Hered Size:         1.062 inches 1st end         Stratest Pressure:         2.000.0 pounds per square inch         Hered Size:         2.000.0 pounds per square inch         Stratest Pressure:         2.000.0 pounds per square inch         Hered Si	Outside Diameter:
6.500 inches Exterior Color: Natural Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximum Operating Pressure: 1000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Corrosion resistant Electrostatic Test Pressure: 2000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Corrosion resistant	1.031 inches
Exterior Color:   Natural   Connection Style:   Swivel nut flare 1st end   End Connection Design:   Straight 1st end   Connection Type:   Threaded internal tube 1st end   Features Provided:   Electrostatic discharge capability   Thready Qty Per Inch (tpi):   12 1st end   Burst Test Pressure:   4000.0 pounds per square inch   Layer Composition And Location:   Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic   Maximum Operating Pressure:   1000.0 pounds per square inch   Exter Strees   1002 inches 1st end   Seat Angle:   37.0 degrees 1st end   Hydrostatic Test Pressure:   2000.0 pounds per square inch   Corrosion resistant   Pressure:   2000.0 pounds per square inch   Corrosin resistant Exter Strees   Seat Angle:   37.0 degrees 1st end   Hydrostatic Test Pressure:   2000.0 pounds per square inch   Corrosion resistant	Minimum Inside Bending Radius:
Natural         Connection Style:         Swiwel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic         Maximum Operating Pressure:         1000.0 pounds per square inch         Ender Size:         1.062 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         2000.0 pounds per square inch         Lydrostatic Test Pressure:         2000.0 pounds per square inch         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         2000.0 pounds per square inch         Corrosion resistant         Incer Covering Environmental Protection:         Corrosion resistant	6.500 inches
Conection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Corrosion resistant	Exterior Color:
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Corrosion per square inch Corrosion resistant	Natural
End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Electrostatic discharge capability         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         4000.0 pounds per square inch         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic         Maximum Operating Pressure:         1000.0 pounds per square inch         Thread Size:         1.062 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         2000.0 pounds per square inch         Corrosion presistant         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         2000.0 pounds per square inch         Outer Covering Environmental Protection:         Corrosion resistant	Connection Style:
Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:4000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, syntheticMaximum Operating Pressure:1000.0 pounds per square inchStread Size:1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchStread Size:1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchCorrosion resistant Stread Size:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchStread Size:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchCorrosion resistantProtection:Corrosion resistantStread Covering Environmental Protection:Corrosion resistantCorrosion resistantCorrosion resistantStread Condition:	Swivel nut flare 1st end
Conection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Corrosion resistant Protection: Corrosion resistant	End Connection Design:
Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Curosion resistant Protection: Corrosion resistant	Straight 1st end
Features Provided:Electrostatic discharge capabilityThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:4000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, syntheticMaximum Operating Pressure:1000.0 pounds per square inchThread Size:1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchCorrosion resistant steel wire and 1st layer molded rubber, syntheticDifference1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchCorrosion resistantCorrosion resistantInter Covering Environmental Protection:Corrosion resistantInside Surface Condition:	Connection Type:
Electrostatic discharge capability Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Cuter Covering Environmental Protection: Corrosion resistant Inside Surface Condition:	Threaded internal tube 1st end
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant	Features Provided:
12 1st end Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition:	Electrostatic discharge capability
Burst Test Pressure: 4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant	Thready Qty Per Inch (tpi):
4000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition:	12 1st end
Layer Composition And Location:Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, syntheticMaximum Operating Pressure:1000.0 pounds per square inchThread Size:1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantInside Surface Condition:	Burst Test Pressure:
Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition:	4000.0 pounds per square inch
Maximum Operating Pressure:1000.0 pounds per square inchThread Size:1.062 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:2000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantInside Surface Condition:	Layer Composition And Location:
1000.0 pounds per square inch Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition:	Outer layer braided corrosion resistant steel wire and 1st layer molded rubber, synthetic
Thread Size: 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition:	Maximum Operating Pressure:
1.062 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition:	1000.0 pounds per square inch
Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition:	Thread Size:
37.0 degrees 1st end Hydrostatic Test Pressure: 2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition:	1.062 inches 1st end
Hydrostatic Test Pressure:         2000.0 pounds per square inch         Outer Covering Environmental Protection:         Corrosion resistant         Inside Surface Condition:	Seat Angle:
2000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition:	37.0 degrees 1st end
Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition:	Hydrostatic Test Pressure:
Corrosion resistant Inside Surface Condition:	2000.0 pounds per square inch
Inside Surface Condition:	Outer Covering Environmental Protection:
	Corrosion resistant
	Inside Surface Condition:
Smooth	Smooth



Measuring Method And Length:

15.750 inches working

## Media For Which Designed:

Fuel/oil, hydrocarbon single response

## Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A542a0