NSN 4720-00-068-5897

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-068-5897 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.625 inches **Minimum Inside Bending Radius:** 6.000 inches **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal pipe 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, chloroprene and 1st layer braided cotton cord **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 0.375 inches 1st end Seat Angle: 30.0 degrees 2nd end **Hydrostatic Test Pressure:** 500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 32.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Nptf 2nd end

N/a

Shelf Life:

NSN 4720-00-068-5897

Nonmetallic Hose Assembly - Page 2 of 2



		• .					
	In	iŧ	Of	MAG	200		ω.
•	,,,	ıL	v.	IAIC	as	u	┏.

--

Demilitarization:

No

Fiig:

A542a0