NSN 4720-00-068-9030

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-068-9030

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -350.0 degrees fahrenheit and 600.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.429 inches |
| Minimum Inside Bending Radius: |
| 1.630 inches |
| Inner Conveying Tube Style: |
| Annular close-pitch corrugated |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 9500.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Measuring Method And Length: |
| 23.250 inches working |
| Thread Series Designator: |
| Unf 2nd end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4720-00-068-9030

Metallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0