## NSN 4720-00-068-9384

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-068-9384

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Tempurature Rating:
-65.0 degrees fahrenheit single response and 375.0 degrees fahrenheit single response
Minimum Inside Bending Radius:
3.500 inches
Exterior Color:
Silver
Angle Between Rigid Elbow Fittings In Deg:
90.0
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
16 1st end
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire
Outer layer braided corrosion resistant steel wire
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1250.0 pounds per square inch
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1250.0 pounds per square inch  Thread Size:
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1250.0 pounds per square inch  Thread Size:  0.750 inches 1st end
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1250.0 pounds per square inch  Thread Size:  0.750 inches 1st end  Seat Angle:
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1250.0 pounds per square inch  Thread Size:  0.750 inches 1st end  Seat Angle:  45.0 degrees 2nd end
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1250.0 pounds per square inch  Thread Size:  0.750 inches 1st end  Seat Angle:  45.0 degrees 2nd end  Flow Angle:
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1250.0 pounds per square inch  Thread Size:  0.750 inches 1st end  Seat Angle:  45.0 degrees 2nd end  Flow Angle:  90.0 degrees 2nd end
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1250.0 pounds per square inch  Thread Size:  0.750 inches 1st end  Seat Angle:  45.0 degrees 2nd end  Flow Angle:  90.0 degrees 2nd end  Inside Surface Condition:
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1250.0 pounds per square inch  Thread Size:  0.750 inches 1st end  Seat Angle:  45.0 degrees 2nd end  Flow Angle:  90.0 degrees 2nd end  Inside Surface Condition:  Smooth
Outer layer braided corrosion resistant steel wire  Maximum Operating Pressure:  1250.0 pounds per square inch  Thread Size:  0.750 inches 1st end  Seat Angle:  45.0 degrees 2nd end  Flow Angle:  90.0 degrees 2nd end  Inside Surface Condition:  Smooth  Measuring Method And Length:

Unf 1st end

**Thread Series Designator:** 

## NSN 4720-00-068-9384

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0