NSN 4720-00-068-9398

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-068-9398 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.312 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.531 inches **Minimum Inside Bending Radius:** 3.000 inches **Exterior Color:** Natural **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1100.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber and 1st layer braided cotton cord **Maximum Operating Pressure:** 275.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end

Hydrostatic Test Pressure:

550.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and mildew resistant and oil resistant and ozone resistant and cold resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

9.250 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-00-068-9398

Nonmetallic Hose Assembly - Page 2 of 2



Γh	read	Series	Designator:
	Loud	OCI ICS	Designator.

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0