Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-069-0757

С	ross Sectional Shape:
R	ound
Т	nread Class:
Зł	o 1st end
Т	nread Direction:
R	ight-hand 1st end
In	side Diameter:
0.	188 inches
Te	empurature Rating:
-1	00.0 degrees fahrenheit single response and 500.0 degrees fahrenheit single response
0	utside Diameter:
0.	312 inches
М	inimum Inside Bending Radius:
2.	000 inches
C	onnection Style:
S	wivel nut flare 2nd end
E	nd Connection Design:
St	traight 1st end
C	onnection Type:
Tł	nreaded internal tube 1st end
Fe	eatures Provided:
EI	ectrostatic discharge capability
В	urst Test Pressure:
12	2000.0 pounds per square inch
La	ayer Composition And Location:
0	uter layer braided corrosion resistant steel wire
Μ	aximum Operating Pressure:
15	500.0 pounds per square inch
TI	nread Size:
0.	438 inches 1st end
S	eat Angle:
37	7.0 degrees 2nd end
H	ydrostatic Test Pressure:
30	000.0 pounds per square inch
FI	ow Angle:
90	0.0 degrees 2nd end
In	side Surface Condition:
Sı	mooth
Μ	easuring Method And Length:
4.	875 inches working
TI	nread Series Designator:
U	njf 1st end

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:

07482-r464c0047al manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0