NSN 4720-00-069-0846

Cross Sectional Shape:

Round

Thread Class:

22.750 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-069-0846

3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.212 inches			
Tempurature Rating:			
-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response			
Outside Diameter:			
0.390 inches			
Minimum Inside Bending Radius:			
1.500 inches			
Exterior Color:			
Natural			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Electrostatic discharge capability and reusable end fittings			
Burst Test Pressure:			
12000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
3000.0 pounds per square inch			
Thread Size:			
Thread Size: 0.438 inches 1st end			
0.438 inches 1st end			
0.438 inches 1st end Seat Angle:			
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end			
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure:			
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch			
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection:			
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant			

NSN 4720-00-069-0846

Nonmetallic Hose Assembly - Page 2 of 2



	•		
I hraad	Series	I Jaciui	12t∩r∙
ııııcau	061163	Desidi	iatoi.

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0