NSN 4720-00-069-2543

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

20.000 inches working

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-069-2543

Inside Diameter:
0.406 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.782 inches
Minimum Inside Bending Radius:
6.750 inches
Exterior Color:
Natural
Connection Style:
Swivel nut with compression sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:

NSN 4720-00-069-2543

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

W/asbest0sshield0uterc0vering

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0