NSN 4720-00-069-5762

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-069-5762

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.200 inches |
| Tempurature Rating: |
| 65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response |
| Outside Diameter: |
| |
| 0.250 inches |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer molded polytetrafluoroethylene |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 6000.0 pounds per square inch |
| Measuring Method And Length: |
| 10.500 inches excluding end fittings |
| Thread Series Designator: |
| Unf 1st end |
| Fsc Application Data: |
| Hydraulic installation, airframe |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A542a0