Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-069-9317

| Cross Sectional Shape: | |
|---|--|
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.406 inches | |
| Tempurature Rating: | |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| 0.766 inches | |
| Minimum Inside Bending Radius: | |
| 4.625 inches | |
| Exterior Color: | |
| Black | |
| Connection Style: | |
| Swivel nut flare 1st end | |
| End Connection Design: | |
| Straight 2nd end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Burst Test Pressure: | |
| 8000.0 pounds per square inch | |
| Layer Composition And Location: | |
| 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord | |
| Maximum Operating Pressure: | |
| 2000.0 pounds per square inch | |
| Thread Size: | |
| 0.750 inches 1st end | |
| Seat Angle: | |
| 37.0 degrees 1st end | |
| Hydrostatic Test Pressure: | |
| 4000.0 pounds per square inch | |
| Flow Angle: | |
| 90.0 degrees 1st end | |
| Outer Covering Environmental Protection: | |
| Mildew resistant and oil resistant | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 31.000 inches working | |
| | |

AeroBase Group

Media For Which Designed:

Air and alcohol, ethyl and hydraulic fluid and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Or Standard:

8 size

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0