

View Online at <https://aerobasegroup.com/nsn/4720-00-069-9338>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Outside Diameter:**

0.750 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-3992, type 1, class 1 or 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**First End Fitting Specification/std Data:**

Ms39133-1 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Second End Fitting Specification/std Data:**

-535746-1 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel 2nd end

**Connection Type:**

Threaded external pipe 1st end

**Thready Qty Per Inch (tpi):**

18 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

900.0 pounds per square inch

**First End Swivel Action Capability:**

Included

**Layer Composition And Location:**

Outer layer molded rubber, synthetic

**Thread Size:**

0.250 inches 1st end

**Outer Covering Environmental Protection:**

Mildew resistant and ozone resistant and heat resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

98.000 inches working

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Thread Series Designator:**

Nptf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-3992 spec.