

View Online at <https://aerobasegroup.com/nsn/4720-00-069-9338>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Outside Diameter:

0.750 inches

Hose Or Tubing Specification/std Data:

Mil-h-3992, type 1, class 1 or 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Ms39133-1 standard (includes industry or association standards, individual manufactureer standards, etc.).

Second End Fitting Specification/std Data:

-535746-1 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Plain 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel 2nd end

Connection Type:

Threaded external pipe 1st end

Thready Qty Per Inch (tpi):

18 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

900.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

Outer layer molded rubber, synthetic

Thread Size:

0.250 inches 1st end

Outer Covering Environmental Protection:

Mildew resistant and ozone resistant and heat resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

98.000 inches working

Special Features:

Inner conveying tube material-rubber, synthetic

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-3992 spec.