NSN 4720-00-070-2704

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-070-2704

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.344 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.547 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
6000.0 pounds per square inch
6000.0 pounds per square inch Layer Composition And Location:
Layer Composition And Location:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire Maximum Operating Pressure:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.562 inches 1st end
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Abrasion resistant and corrosion resistant
Layer Composition And Location: Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire Maximum Operating Pressure: 1000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Abrasion resistant and corrosion resistant Inside Surface Condition:

Media For Which Designed:

Air and fuel/oil, hydrocarbon single response

NSN 4720-00-070-2704

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series	Designator:
---------------	--------------------

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0