NSN 4720-00-071-2270

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-071-2270

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.215 inches
Minimum Inside Bending Radius:
7.380 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3200.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and outer layer braided textile yarn and 1st layer braided textile yarn
Maximum Operating Pressure:
800.0 pounds per square inch
Thread Size:
1.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1600.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:

12.000 inches

NSN 4720-00-071-2270

Nonmetallic Hose Assembly - Page 2 of 2



	Media	For	Which	Design	ned:
--	-------	-----	-------	--------	------

Hydraulic fluid single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0