

View Online at <https://aerobasegroup.com/nsn/4720-00-071-8757>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

2.000 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 257.0 degrees fahrenheit single response

**Outside Diameter:**

2.480 inches

**Minimum Inside Bending Radius:**

12.000 inches

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external pipe 1st end

**Thready Qty Per Inch (tpi):**

11-1/2 1st end

**Burst Test Pressure:**

400.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided textile yarn and outer layer molded rubber, synthetic and 1st layer braided textile yarn

**Maximum Operating Pressure:**

100.0 pounds per square inch

**Thread Size:**

2.000 inches 1st end

**Hydrostatic Test Pressure:**

200.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

108.000 inches working

**Special Features:**

Textile braids are combined with wire spiraled throughout

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Nptf 1st end

**Fsc Application Data:**

Arresting gear, aircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0