

View Online at <https://aerobasegroup.com/nsn/4720-00-071-8757>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

2.000 inches

Temperature Rating:

-40.0 degrees fahrenheit and 257.0 degrees fahrenheit single response

Outside Diameter:

2.480 inches

Minimum Inside Bending Radius:

12.000 inches

Connection Style:

Plain 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external pipe 1st end

Thready Qty Per Inch (tpi):

11-1/2 1st end

Burst Test Pressure:

400.0 pounds per square inch

Layer Composition And Location:

2nd layer braided textile yarn and outer layer molded rubber, synthetic and 1st layer braided textile yarn

Maximum Operating Pressure:

100.0 pounds per square inch

Thread Size:

2.000 inches 1st end

Hydrostatic Test Pressure:

200.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

108.000 inches working

Special Features:

Textile braids are combined with wire spiraled throughout

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 1st end

Fsc Application Data:

Arresting gear, aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0