NSN 4720-00-071-9095

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-071-9095

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
maximum operating recours.
1500.0 pounds per square inch
1500.0 pounds per square inch
1500.0 pounds per square inch Thread Size:
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle:
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 2nd end
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure:
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 6000.0 pounds per square inch
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 6000.0 pounds per square inch Flow Angle:
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 6000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 6000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection:
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 6000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 6000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr:
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 6000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8

NSN 4720-00-071-9095

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 10.200 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: -Demilitarization: No

Fiig: A542a0