NSN 4720-00-073-1820

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-073-1820

Cross Sectional Shape:					
Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.625 inches					
Tempurature Rating:					
-67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response					
Outside Diameter:					
0.906 inches					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
700.0 pounds per square inch					
Layer Composition And Location:					
Outer layer molded rubber, synthetic and 1st layer braided cotton cord					
Maximum Operating Pressure:					
150.0 pounds per square inch					
Thread Size:					
0.875 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
250.0 pounds per square inch					
Outer Covering Environmental Protection:					
Fuel resistant and oil resistant					
Vacuum In Torr:					
508.0					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
50.000 inches working					
Media For Which Designed:					
Fuel/oil, hydrocarbon single response					
Thread Series Designator:					

Unf 1st end

NSN 4720-00-073-1820

Nonmetallic Hose Assembly - Page 2 of 2



Sı	pe	cifi	cati	on	Data:
•	\sim	•••	outi	•••	Dutu.

88044-an6270 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0