## NSN 4720-00-075-0000

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-075-0000

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 2b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.875 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response   |
| Outside Diameter:   |
| 1.200 inches  |
| Minimum Inside Bending Radius:  |
| 7.380 inches  |
| Exterior Color:   |
| Black   |
| End Application:  |
| Clark model 290m; tractor, wheeled, ind., diesel driven; med dbp, nsn 2420000889384, w/rops nsn 2420010590090 |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 2nd end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Thready Qty Per Inch (tpi):   |
| 12 1st end  |
| Burst Test Pressure:  |
| 1500.0 pounds per square inch   |
| Layer Composition And Location:   |
| 2nd layer braided steel wire and outer layer rubber impregnated fabric and 1st layer braided fabric           |
| Maximum Operating Pressure:   |
| 375.0 pounds per square inch  |
| Thread Size:  |
| 0.750 inches 2nd end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 750.0 pounds per square inch  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |

44.500 inches

## NSN 4720-00-075-0000

Nonmetallic Hose Assembly - Page 2 of 2



| Media For Which Designe | Which Designe | ed |
|-------------------------|---------------|----|
|-------------------------|---------------|----|

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Un 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A542a0