NSN 4720-00-075-0000

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-075-0000

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.200 inches
Minimum Inside Bending Radius:
7.380 inches
Exterior Color:
Black
End Application:
Clark model 290m; tractor, wheeled, ind., diesel driven; med dbp, nsn 2420000889384, w/rops nsn 2420010590090
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
1500.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and outer layer rubber impregnated fabric and 1st layer braided fabric
Maximum Operating Pressure:
375.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
750.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:

44.500 inches

NSN 4720-00-075-0000

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designe	Which Designe	ed
-------------------------	---------------	----

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0