

View Online at <https://aerobasegroup.com/nsn/4720-00-075-0519>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.250 inches and 0.281 inches

Temperature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.563 inches and 0.625 inches

Minimum Inside Bending Radius:

3.000 inches

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal pipe 1st end

Burst Test Pressure:

800.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, ethylene propylene and 1st layer molded rubber, synthetic

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Hydrostatic Test Pressure:

400.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.750 inches and 15.250 inches

Thread Series Designator:

Npt 1st end

Specification Data:

81349-mil-h-24520 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0