Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-075-4748

Cross Sectional Shape:
Round
Thread Class:
2a 1st end Thread Direction:
Right-hand 1st end
Inside Diameter:
0.190 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
3.500 inches
Connection Style:
Swivel nut, inverted flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 1st end
Thready Qty Per Inch (tpi):
24 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided wire
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
45.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
10.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon and water single response
Thread Series Designator:
Uns 1st end
Shelf Life:
N/a

## NSN 4720-00-075-4748

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0